

```
/***/
```

```
EditableBulletList  
(optional) values : list  
(optional) noValuesLabel : str  
(optional) editLabel : str  
(optional) addLabel : str  
(optional) saveLabel : str  
(optional) cancelLabel : str  
(optional) publish : str  
(optional) class : str  
(optional) readOnly : bool  
(optional) readOnlyAlert : str  
(optional) message : map
```

```
***/
```

```
// TODO (steveb):  
// 1) reset the contents of the textboxes when the edit operation is  
canceled  
// 2) update the bullet list after save is confirmed
```

```
// read parameters  
var values = $values ?? [ ];  
var novalueslabel = $novalueslabel ?? 'There are no values.';  
var editlabel = $editlabel ?? 'edit';  
var addlabel = $addlabel ?? 'add';  
var savelabel = $savelabel ?? 'save';  
var cancellabel = $cancellabel ?? 'cancel';  
var channel = $publish ?? 'default';  
var class = $class;  
var readonly = $readonly ?? user.anonymous;  
var readonlyalert = $readonlyalert ?? 'You must login to edit these  
values.';  
var message = $message ?? { };
```

```
// render controls
```

```
<div id=@div class=(class)>

    // check if the edit button should be enabled
    if(readonly) {
        <input type="button" value=(editlabel) id=@edit ctor="
            when($this.click) alert({{ readonlyalert }});
        "/>
    } else {
        <input type="button" value=(editlabel) id=@edit ctor="
            when($this.click) @toggle();
        "/>
    }

    // render current values as a bulleted list
    <div id=@displayspan>
        if(#values == 0) {
            <div id=@resizeonedit>
                novalueslabel
            </div>
        } else {
            <ul>
                foreach(var value in values) {
                    <li> value </li>
                }
            </ul>
        }
    </div>

    // render the edit form
    <form id=@changeform>
        if(#values != 0) {
            foreach(var value in values) {
                <textarea>
                    value
                </textarea>
            }
        } else {
            <textarea />
        }

        // separate the input boxes from the controls
        <div class="cleardiv"> &nbsp; </div>

        // render the add button
        <input type="button" id=@add value=(addlabel) ctor="
            when($this.click) $('#' + {{ @changeform }} + '
textarea:last').after('<textarea></textarea>');
        "/>

        // render the save button
```

```

    &nbsp;;
<input type="button" id=@save value=savelabel ctor=
    when($this.click) {
        var newvalues = [ ];
        $('#' + {{ @changeform }} + ' textarea').each(function() {
            var val = $(this).val();
            if(val != '') newvalues.push(val);
        });
        var msg = {{ message }};
        msg.values = newvalues;
        msg.completed = function() { @toggle(); };
        Deki.publish({{ channel }}, msg);
    }
"/>

// render the cancel button
&nbsp;;
<input type="button" id=@cancel value=cancellabel ctor=
    when($this.click) @toggle();
"/>
</form>
</div>

// script
<script type="text/jem">
when(@toggle) {
    $('#' + {{ @changeform }} + ',#' + {{ @displayspan }} + ',#' + {{ @edit }}).slideToggle();
    var resizeonedit = $('#' + {{ @resizeonedit }});
    if(resizeonedit.css('padding-top') == '0px') {
        resizeonedit.css('padding-top', '1.6em');
    } else {
        resizeonedit.css('padding-top', '0px');
    }
}
"</script>

// styles
<style type="text/css">
#" .. @resizeonedit .. " {
    padding-top: 1.6em;
}
#" .. @changeform .. " {
    display: none;
}
#" .. @changeform .. " textarea {
    width: 50%;
    float: left;
    margin-bottom: 5px;
}

```

```
#" .. @div .. " .cleardiv {  
    height:1px;  
    clear:both;  
}  
"</style>
```